

# WIRELESS WIFI NVR KIT

7" Touch Screen  
with 2 WiFi Cameras

express one   
.co.uk



## Product Description

The 7" high-definition touch screen network video recorder is designed with lightweight and easy to place. It can support 4 channels of real-time input at the same time, support motion detection recording, and store video in TF card.

- 1CH playback
- Supports dual WIFI
- Supports IOS, Android mobile APP remote access, remote playback and alarm push function.
- Camera can connect recorder through wireless code match.
- NVR can support 4CH of 2MP, H264/H265 pure wireless camera input, battery camera and doorbell.



SPECIFICATION	LCD-KIT2MP
<b>7" HD TOUCH SCREEN NETWORK RECORDER SPECIFICATION</b>	
Operating System	Embedded Linux operating system
Video Input	4 channels x 1080P, pure wireless camera
Video Output	Size: 7" Resolution: 1024 x600 Supports touch screen operation
Audio Input	Built-in mic-phone, supports voice intercom with IPC
Audio Output	Supports speaker output (built-in speaker)
<b>VIDEO CODING PARAMETERS</b>	
Video Compression Standard	Standard H.264, H265
Video and Playback Performance	4 channel 1080P video 1 channel 1080P playback
Video Bit Rate	256 Kbps -- 3.0 Mbps
Dual Code Stream	Support
Audio Compression Standard	AAC
<b>VIDEO MANAGEMENT</b>	
Video Mode	PIR motion detection recording, automatic overlay loop recording
<b>STORAGE METHOD</b>	
Video Storage Method	TF card recording storage
<b>EXTERNAL INTERFACE</b>	
Battery Switch	Select the power supply to NVR by built-in battery or DC jac
USB Interface	1 USB 2.0 interface (supports USB flash drive upgrade, and mouse)
2.4G Dual WIFI Interface	Support IPC code and connection, and wireless Internet access
TF Card Holder	Maximum support 128G
<b>OTHER</b>	
Power Supply	DC 5V 2.5A
Power Consumption	≤8.0W
Working Temperature	-10°C ~ +50°C
Machine Size	191 x 123 x 31.5mm
Machine Weight	≤500g

# WIRELESS WIFI NVR KIT

7" Touch Screen  
with 2 WiFi Cameras

express one   
.co.uk



SPECIFICATION	LCD-KIT2MP
<b>CAMERA SPECIFICATION</b>	
Sensor	2MP 1/2.9" 1/3" CMOS sensor
Light Sensor	Light sensor resistance
IR-Cut	Supported
Lens	4mm
Mix Luxury	Black white 0 Lux
IR Light	6pcs array ir light / suggested use in 5-10m
Light Mode	Day / night / black white / auto
<b>INTERFACE</b>	
Audio Input	Built-in mic
Audio Output	Built-in speaker
Reset	With reset button/used to match code/reset
wifi	Built in 2.4G antenna
TF Card	Supports : max 128G
RJ45 Interface	10-100M self-adaptive
Indicator Light	At bottom of cable/LED flash means AP mode/LED keep light means connection well
<b>COMPRESS STANDER</b>	
Video Compress Stander	H.264 Main Profile
Audio Compress Stander	AAC
<b>IMAGE/CODE STREAM</b>	
Resolution	1920 x 1080 (1080P)
Code Steam	1920 x 1080@15F main stream 640 x 360@15F sub stream
OSD	Supported
<b>INTERNET</b>	
Internet Protocol	TCP / IP / HTTP / ICMP / UDP / ARP / IGMP /DHCP / DNS / NTP / RTSP
Onvif	V2.4
<b>ENVIRONMENT</b>	
Working Temperature/Moisture	-20°C ~ +50°C / 20% ~ 80%
Consumption	12V-1A DC
Power In	3W
<b>OTHERS</b>	
PIR	Suggested use in 7meter in 60° area