

LED-HDMI2106D

21.5" MONITOR



Features :

- Industrial level LCD panel, suitable for continuous 24/7 operation
- High fidelity digital processing for a brilliant and vivid video
- 5ms response time for no motion blur, judder or ghosting
- Included desk stand is easily removable for standard VESA mounting
- Support HDMI/VGA/BNC signal input
- Built in speakers



Technical Specification

Model

Model	LED-HDMI2106D
-------	---------------

Display

Screen Size	21.5"
Aspect Ratio	16:9
Resolution	1920x1080 (FHD)
Backlight	LED
Brightness/Luminance	200cd/ m ²
Contrast Ratio	1000:1
Display color	16.7M(8bit)
Viewing Angle(H/V)	178°(H)/178°(V)
Response Time	5ms
Refresh Rate	60Hz

Signals

Input	VGAx1, HDMIx1, BNCx1, USBx1(for upgrading), Audiox1	
Output	BNCx1	
	Speaker	3Wx2

General

Power Supply	AC100~240V (+/-10%), 50/60 Hz
--------------	-------------------------------

Consumption (Standard)	≤30W	
Consumption (Standby)	≤0.5W	
Type	Internal	
Net Weight	3.2 kg (7.1lb)	
Gross Weight	3.7kg (8.2lb)	
Bezel Width	13.5mm (U/R/L), 19.01mm (B)	
VESA	75x75mm (3.0"x3.0")	
Dimension without base (WxHxD)	502.8x299.8x47.6mm (19.8"x11.8"x1.9")	
Package(WxHxD)	578x420x116mm (22.8"x16.5"x4.6")	
Work Environment	Temperature	0°C~ 40°C
	Humidity	10%~85%

Accessory

Standard	HDMI cable, power cable, pedestal
Optional	Hanging bracket

Dimensions(mm)

