



# Motorised Lens Bullet Camera

CODE: MBULLETVIP4K3-VG-A

IP

8<sup>4K</sup>  
MP

NDA  
Compliant



PoE  
Support



4K/8MP  
Resolution



70m IR  
Range



Triple Stream  
Support

## Camera

Image Sensor	1/2.7" CMOS
Video Compression	H.265 / H.264
Resolution	8MP, 6MP, 5MP (1 to 20fps)
Electronic Shutter	1/25s to 1/100,000s
Minimum Illumination	0.11 lux at F1.4 (AGC on); 0.032 lux at F1.2 (AGC on); 0 lux with IR
IR Range	70m
Lens	2.8mm to 12mm
Field of View	<b>Horizontal:</b> 102.7° to 32.2°
Focus	Motorised
Image Correction	BLC, HLC, WDR, Defog, Digital NR

## Interfaces

Network	RJ45
Audio	1CH audio input; 1CH audio output
Alarm	1CH alarm input; 1CH alarm output
Storage	Micro SD card slot (supports up to 256GB)
Reset Button	Yes

## Functions

Remote Monitoring	SuperLive Plus Mobile App / NVMS (used with Viper NVR)
Online Connection	Simultaneous multi-stream real time transmission
Maximum Users for Monitoring	Up to 3 users (simultaneous)
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, PPPoE, DDNS, SMTP, FTP, 802.1x, UPnP, HTTP, HTTPS, QoS
Interface Protocol	ONVIF



# Motorised Lens Bullet Camera

CODE: MBULLETVIP4K3-VG-A

IP

8<sup>4K</sup>  
MP

## Functions (continued)

Alarm Events	Video Motion Detection, Video Exception, SD Card Error, SD Card Full
AI Events	Line Crossing Detection, Region Intrusion Detection, Scene Change Detection
Additional Functions	Watermark, Video Mask, Heartbeat, Password Protection

## Parameters & Dimensions

Power Supply	DC12V / PoE
Power Consumption	< 9.5W
Operating Environment	Temperature: -30°C to +60°C; Humidity: Less than 95% (non-condensing)
Storage Environment	Temperature: -30°C to +65°C; Humidity: Less than 95% (non-condensing)
Dimensions	279.5mm x 100.3mm x 88.9mm
Weight	1.032kg
Installation	Ceiling or wall mounted
Protection Grade	IP67
Certificate	UKCA, CE, FCC, PSTI 2023, RoHS, WEEE, REACH (EC1907/2006)

## Compatible Accessories



Cable Management Ring  
CODE: VIP-RING-06-WH