

CTX-POESWITCH-POE8GT 11-PORT GIGABIT SWITCH (8x PoE)



* The parameters and datasheets below can only be applied to V2.0 (version 2.0)

- Intelligent PoE
- 8-pin assignment PoE power supply
- Long distance PoE
- PoE watchdog
- BT 90W
- All-giga ports
- Wide working temperature



System Overview

DH-PFS3211-8GT-120 is an unmanaged hardened PoE Switch with 8× 10/100/1000 Mbps PoE Ports. It has 8 × 10/100/1000 Mbps Ethernet ports , 2 × 1000 Mbps uplink SFPs and 1 × 10/100/1000 Mbps Ethernet uplink ports. The product is equipped with two types of transmission modes (Extend Mode On/Extend Mode Off). The red port supports IEEE802.3bt and the Hi-PoE standards. The maximum power consumption is 120W. It also supports PoE watchdog to avoid the need for manual maintenance and restart.

Functions

Intelligent PoE

Provides control over power consumption and offers real-time monitoring to ensure power supplies receive priority with important ports and to prevent malfunctions caused by changes in power consumption. Supports ultra wide power supplies and is able to adapt to IPC power fluctuations.

BT 90W

The red ports support IEEE802.3af, IEEE802.3at, IEEE802.3bt and Hi-PoE standards, with a maximum output power consumption rate of 90W per port. Suitable for powering high-power devices.

PoE Watchdog

Adopts innovative PoE Watchdog technology. PoE Watchdog can be switched on by dialing or turning on the WEB switch. It enables the switch to automatically detect port status and restart failed ports to recover connection in case of IPC connection exception. This enables intelligent operation and maintenance management, effectively reducing manual maintenance costs.

Long Distance PoE

By dialing or enabling long-range transmission on the WEB interface, the transmission distance of a PoE port can be up to 250m, meeting the requirements of wired transmission (bandwidth reduced to 10 Mbps).

8-pin Assignment PoE Power Supply

Supports 8-pin simultaneous power supply (1/2/4/5 positive, 3/6/7/8 negative). Signal lines and idle lines supply power at the same time. Compatibility with IPC is enhanced. Cable loss is reduced. Loading capacity is increased.

Specification

Hardware Feature

Ethernet Port	Port 1-8: 8 × RJ-45 10/100/1000 Mbps (PoE) Port 9-10: 2 × SFP 1000 Mbps (uplink) Port 11: 1 × RJ-45 10/100/1000 Mbps (uplink)
PoE Power Consumption	Port 1-2≤ 90W, Port 3-8 ≤30W, Total≤120W
Power Consumption	Idling: 5 W Full load: 120 W
Standard	IEEE802.3/IEEE802.3u/IEEE802.3X/IEEE 802.3az/IEEE 802.3ab
PoE	
PoE Protocol	IEEE 802.3af/ IEEE 802.3at/ Hi-PoE/IEEE 802.3bt
Power Supply Pin	1,2,4,5 (V+),3,6,7,8 (V-)
Long Distance	250 m long distance PoE transmission
PoE Power Management	Yes
PoE Watchdog	Yes

Performance

Switching Capacity	33 Gbps
Packet Forwarding Rate	16.37 Mpps
Packet Buffer Memory	1.75 Mbit
Flow Control	Enable by default
Working Temperature	-30 °C to +65 °C (-22°F to +149°F)
Application Humidity	5%~95% (RH)

General

Power Input	48 V- 57 V DC
Lighting Protection	Common mode 4 kV Differential mode 2 kV
ESD Protection	Air discharge 8 kV Contact discharge 6 kV
Wall-mount Installation	Yes
Anti-theft Lock Hole	Yes
Weight	0.67 kg (1.48 lb)
Dimension	150mm × 110mm × 42mm (5.91" × 4.33" × 1.65")

Transmission Performance:

Switch power supply voltage 53V.
CAT5E/CAT6. Max. DC resistance < 10Ω/100m

Cable(m)	Load Capacity(W)	Bandwidth(Mbps)
IEEE802.3bt 90W		
100	71.3	100
150	62	10
200	51	10
250	40	10


Hi-PoE 60W

Cable(m)	Load Capacity(W)	Bandwidth(Mbps)
100	53	100
150	50	10
200	47	10
250	37	10

IEEE802.3at 30W

Cable(m)	Load Capacity(W)	Bandwidth(Mbps)
100	25.5	100
150	25.5	10
200	25.5	10
250	25.5	10

Installation



Dimensions (mm[inch])

