

# Al Motorised Lens Vandal Dome Camera

**CODE:** MVANVIP4KE3-VG-A











People & Vehicle Detection



Advanced Al Functions



50m IR Range



Triple Stream
Support



Image Sensor	1/2.8" CMOS
Video Compression	H.265+ / H.265 / H.264+ / H.264
Resolution	8MP, 6MP, 5MP, 4MP, 2K, 3MP, 2MP
ricsolution	
	(1 to 25fps)
Minimum Illumination	0.01 lux at F1.2 (AGC on);
	0.015 lux at F1.4 (AGC on);
	0 lux with IR
IR Range	50m
n i nange	33111
Lens	2.8mm to 12mm
25116	
Field of View	Horizontal: 96° to 32°
	Vertical: 64° to 18.4°
	TO THOUSE TO TOTAL
	<b>Diagonal:</b> 103.8° to 36.5°
Focus	Motorised
1 0000	Wotonsea
Image Correction	BLC, HLC, WDR, Defog, Digital NR
9	===, ::==, ::=::, 30.0g, 3.g.ta. : :::

### Interfaces

Network	RJ45
Video Output	CVBS Output (BNC x1)
Audio	1CH audio input; 1CH audio output 1CH built-in microphone
Alarm	1CH alarm input; 1CH alarm output
Storage	Micro SD card slot (supports up to 256GB)
Reset Button	Yes

# Functions Functions

Remote Monitoring	SuperLive Plus Mobile App / NVMS (used with Viper NVR)
Online Connection	Simultaneous multi-stream real time transmission
Maximum Users for Monitoring	Up to 10 users (simultaneous)
Network Protocol	UDP, IPv4, IPv6, DHCP, NTP, RTSP, RTP, RTCP, ICMP, IGMP, PPPoE, DDNS, SMTP, FTP, SNMP, HTTP, 802.1x, UPnP, HTTPS, QoS



# Al Motorised Lens Vandal Dome Camera

CODE: MVANVIP4KE3-VG-A







Interface Protocol	ONVIF
Alarm Events	Video Motion Detection, Video Exception, SD Card Error, SD Card Full
Al Events	Line Crossing Detection, Region Intrusion Detection (People & Vehicle), Video Abnormality, Face Detection & Capture, Exception Detection
Additional Functions	Watermark, Video Mask, Heartbeat, Password Protection, Image Distortion Correction





Cable Management Ring CODE: VIP-RING-05-WH



#### Parameters & Dimensions

Power Supply	DC12V / PoE
PoE	IEEE802.3af
Power Consumption	< 10.5W
Operating Environment	Temperature: -30°C to +60°C; Humidity: Less than 95% (non-condensing)
Storage Environment	Temperature: -30°C to +65°C; Humidity: Less than 95% (non-condensing)
Dimensions	Ø141mm x 100.2mm
Weight	0.89kg
Installation	Ceiling or wall mounted
Protection Grade	IP67 & IK10
Certificate	UKCA, CE, FCC, PSTI 2023, RoHS, WEEE, REACH (EC1907/2006)