



# Carbon Monoxide Detector

CODE: QFS-CO



## Features

- LCD screen
- Carbon Monoxide [CO] alarm
- Sealed tamperproof Lithium integrated battery
- Compliant with EN50291-1:2018
- Alarm sounder [85dB]



Specification	QFS-CO
Alarm Volume	>85dB
Alarm Mode	LCD, LED & buzzer
Wake-Up Cycle	8 seconds
Battery Type	2pcs 3V Lithium battery
Battery Model	FR14505
Execution Standard	EN50291-1.2018
CO Sensor Type	CO electrochemical sensor
Interface / Display	Test/hush button on front / LCD display
Standby Current	14uA
Power Supply	DC6V
Product Life	10 years [5 year product warranty]
Working Conditions	-10°C to +50°C, 30% to 90%RH [humidity]
Installation	Wall hanging
Product & Battery Life	10 years
Included in Box	2x screw, 2x positioning screw, 1x easy-install bracket
Dimensions	129mm x 74mm x 38mm
Weight	140g





# Carbon Monoxide Detector

CODE: QFS-CO

## Functions

Initialisation	One beep, constant green LED flash, display counts down 60 seconds	
Normal	Green LED flash once [50 seconds]	
Alarm	Red LED flashes quickly, buzzer sound	
Mute	Red LED flashes, no sound; If after 9 minutes the CO concentration doesn't return to normal threshold, the alarm will reactivate automatically. Otherwise, the device returns to normal standby state	
Fault	Yellow LED flashes twice [50 seconds], Accompanied by 2x buzzer sounds	
Low Voltage	Yellow LED flashes once [50 seconds], accompanied by 3x buzzer sounds	
Test	Press the test button to show status on demand (make sure to press at the top)	





# Carbon Monoxide Detector

CODE: QFS-CO

## Alarm Response

	Initial Reaction	Alarm Activation	Hush Function
<30PPM Concentration	Screen lights up & displays current Cconcentration	No alarm	Manual mute can be activated
30 to 50PPM	Red flash every 2 minutes (silent) 	Full alarm after 120min (approx) 	Manual mute can be activated
50 to 100PPM	Red flash every 2 minutes & beep 	Full alarm after 60min (approx)	Manual mute can be activated
100 to 300PPM	Red flash every 2 minutes & beep 	Full alarm after 60min (approx)	Manual mute can be activated
>300PPM	Hush function will not work due to critical levels 	Full alarm within 3min (approx)	Manual mute can be activated

### **WARNING**



The alarm's mute function ('Hush' button) can only be activated if concentration is below 300PPM. However, it is crucial that you do not ignore any alarm from the detector, as Carbon Monoxide is highly toxic and can induce serious side effects, potentially within minutes.




# Carbon Monoxide Detector

CODE: QFS-CO

## Installation

- 1) Take Out Installation Tools
- 2) Determine Installation Position (Do Not Obstruct Air Inlets)




- 3) Fix Wall Bracket to the Alarm, Install Onto Wall with Screws



- 4) Install the Battery & Activate the Device

- 5) Clip Alarm onto the Bracket



- 6) Push Test Button to Ensure Device Operation is Normal

