

Veritas R8

Control Panel with Remote Keypad

Experience a higher level of performance with the Veritas R8 from Texecom. With a host of new features, expect the leading control panel in its class to excel in any installation. Operation is quicker and easier. Programming has been both simplified and extended. The Veritas R8 meets all your needs, and much more.

Outstanding Features

- 8 Fully Programmable Zones Plus Tamper
- Single Button Quick Set Option
- Service Timers (Date Programmable)
- Latching Walk Test Mode
- 2 Programmable Part Set Suites
- Soak Test Suite
- Accepts Up To Six Backlit LED Remote Keypads
- Keypad PA Option (Press 3 & 9 Together)
- Key Switch Facility
- PD6662:2010 Grade 1 Class II



Includes the Veritas LED Remote Keypad
Accepts up to 6 Backlit Veritas LED Remote Keypads

Texecom

Veritas R8



8 Fully Programmable Zones Plus Tamper

The Veritas R8 features 8 fully programmable zones plus an additional global system tamper. Each zone operates in any of the 8 different zone types ensuring exceptional system flexibility.



Accepts Up To 6 Backlit Keypads

With ergonomically designed touchtone backlit keys, the Veritas RKP provides a superior user-interface. Easy to set-up and install, a hinged PCB chassis ensures excellent cable access and simple wiring.



Universal Programming Platform

The Veritas R8 utilises the same intuitive programming platform as the rest of the Veritas Series, ensuring instant product familiarity across the range.

Specifications

Veritas R8 Endstation

Current Consumption:	Quiescent current:	<50mA
	Alarm current:	<150mA
Power Supply:	Mains Supply Voltage Rating:	230VAC/115VAC (±10%)
	Max. Total Current Rating:	1Adc at 230VAC/115VAC (±5%)
	Ripple:	<5%
Dimensions:	282mm x 225mm x 80mm	

Veritas LED Remote Keypad

Electrical:	Operating Voltage:	13.7Vdc nominal, 10.0Vdc min
	Current Consumption:	<70mA
Dimensions:	140mm x 105mm x 35mm	

Veritas R8



European Standards

EMC: Conforms to European Union (EU) Electro-Magnetic Compatibility (EMC) Directive 89/336/EEC (amended by 92/31/EEC and 93/68/EEC).

Approved to BS EN 55022 Class B and BS EN 50130-4 : 1996.

PD6662:2010 & EN 50131 Grade 2x Environmental Class II.

The CE mark indicates that this product complies with the European requirements for safety, health, environmental and customer protection.

Texecom products are protected by UK and International patents, trademarks and registered design rights. UK Registered Design Numbers 1573433, 2041830, 2047440, 2055230 & 2089016.

Veritas is a trademark of Texecom Limited. ©2009 Texecom Limited. (LIT-0078-2)

Veritas 8 – G1 Class II

Best selling stand alone control panel. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads.



Veritas 8 Compact – G1 Class II

Slimline, discreet stand alone control panel. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads.



Veritas R8 – G1 Veritas R8Plus – G2

Best selling control panels with remote keypad. Features 8 fully programmable zones and accepts up to 6 backlit remote keypads. Veritas R8Plus also includes EOL wiring, communicator interface and accepts Veritas Excel LCD keypads.



Veritas Excel – G2 Class II

All the features of the Veritas R8 Plus including an LCD keypad for even easier programming and operation.



Certificate Number: FM 35285



A20090303