

# QVIS® | Passive HD Transceiver for CVI/TVI/AHD

## FEATURES:

- Compatible with HD-TVI, HD-CVI and AHD signal
- Up to 400m for HD-CVI 720P signal
- Up to 250m for HD-CVI 1080P signal
- Up to 250m for HD-TVI 720P signal
- Up to 250m for HD-TVI 1080P signal
- Up to 350m forAHD 720P signal
- Up to 200m for AHD 1 0B0P signal
- Super interference rejection
- Built-in TVS for surge protection
- 60 dB crosstalk and noise immunity

| Model No. | TT-105AP |
|---|---|
| **PROPERTIES** | |
| Transmission Signal | 1 channel |
| Transmission Distance | HDCVI 720P: 400m /1080P: 250m; HDTVI 720P/1080P: 250m; AHD 720P: 350m/1080P: 200m |
| Category Type | UTP CATS /SE/6 |
| Coaxial Video Connector | BNC-M |
| **VIDEO TRANSMISSION PROPERTIES AND PORT** | |
| Twisted-pair Video Connector | Screw interface |
| Compatible Format | HDCVI/HDTVI/AHD |
| Resolution | 720P/1080P |
| Anti-interference | >60db |
| **PROTECTION** | |
| ESD | 1a contact discharge electricity level 3<br>1b air discharge electricity level 3<br>Per: IEC61000-4-2 |
| Coaxial Cable Connector | 2KV(common-code) Per: IECl000-4-5 |
| UTP Cable Connector | 2KV(different-code),4KV (common-code),Per: IEC1000-4-5 |
| **IMPEDANCE** | |
| BNC Male | 75 ohms |
| UTP Cable | 100 ohms |
| **ADDITIONAL** | |
| Shell | ABS |
| Colour | Black |
| N.W. | 18.6G |
| MTBF | >10000H |
| Operating Temperature | -10°C ~ 55°C |
| Storage Temperature | -20°C ~ 70°C |
| Humidity | 0 ~ 95% (non-condensing) |
| Dimension (LxWxH) | 55mmx16mmx19mm |

