

IP66 Rated Enclosure for EVC302GF or EVC302F Outstations Part No. BF359/1



Overview

- An attractive IP66 rated enclosure designed for use with a SigTEL EVC302GF or EVC302F flush mounting disabled refuge controller.
- Includes a handle and mounting plate.
- Measures 200 W x 302 H x 123mm deep.
- Textured RAL 7035 (light grey) finish.
- Also compatible with C-TEC's EP210F remote status units.



More Information



T 01942 322744 E sales@c-tec.co.uk F 01942 829867 W www.c-tec.com





C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



Technical Specifications

Approvals/certifications	Enclosure is UL listed (Issue no. K-4256).
Compatibility	Can house an EVC302GF green or EVC302F stainless steel SigTEL outstation. Also compatible with EP210F Remote Status Units.
Product dimensions (mm)	200 W x 302 H x 123 D mm. Designed for surface mounting only.
Construction & finish	Sheet steel enclosure and door, dipcoat primed, powder-coated on the outside, textured paint (RAL 7035 grey). Also includes a green disabled refuge sticker.
IP Rating	IP66
Weight	2.5kg (enclosure and mounting plate).



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



