

4-8 Way Sounder Controller (ZFP CAST only) Part No. CA739



Overview

- A 4-8 way sounder controller specifically designed for use on a C-TEC CAST ZFP addressable fire alarm system.
- Supplied as a 4 circuit unit extendable to 8 circuits using a CA739PCB.
- Provides 4 or 8 monitored 12.5mA sounder circuits.
- Includes space and connections for an optional fully monitored auxiliary 24V 1.5A CA739PSU to power additional devices.
- Includes an onboard short circuit loop isolator
- Uses one loop address per 4 sounder circuits
- 12.5mA per sounder circuit capacity when loop powered; 300mA per sounder circuit capacity when aux CA739PSU PSU is used.
- Maintains the independent open & short circuit monitoring of all sounder circuits.

More Information

Technical Specifications

| Compatibility | Compatible with C-TEC's CAST ZFP Addressable Fire Panels. This device is NOT compatible with CAST XFP panels. |
|--------------------------------------|--|
| Application/operation | Allows a series of C-TEC's ActiV conventional sounders/VADs to be connected to and contolled by an C-TEC CAST ZFP addressable fire system. |
| Current rating | Max. 12.5mA per circuit (optional 24V 1.5A CA739PSU available to boost alarm current across all circuits) |
| Supply/operating voltage | 22 to 40V DC. |
| Quiescent current | 1.7mA |
| No. of conventional sounder circuits | s 4 (as standard). Expandable to 8 using a CA739PCB. |
| Alarm current | 3mA. |
| Auxiliary relays | None. |
| Indicators | Active (Lit Red): sounder circuit activated; Polling (Flashing Red): communication check with the panel; Fault (Lit Yellow): fault detected on the sounder circuit and/or fault on aux. PSU (if conne |
| Controls | Individual sounder circuit test facility via onboard push buttons. |
| Product dimensions (mm) | 380 W x 235 H x 96D mm. Can be surface or flush mounted. |
| Construction & finish | Plastic lid and base. |
| IP Rating | IP30. |
| | |

😥 🔛 🔐 CC 🚾 🛇

OIHLMA



 T
 01942 322744
 E
 sales@c-tec.co.uk

 F
 01942 829867
 W
 www.c-tec.com

C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom



Weight Operating conditions/temperature

1.5kg approx (without batteries). -10ºC to +55ºC.



T 01942 322744 E sales@c-tec.co.uk **F** 01942 829867 W www.c-tec.com



