

50m2 Domestic TV Lounge Hearing Loop System

Part No. PDA103S



Overview

- Everything you need to create a high quality domestic hearing loop system for bedrooms, living rooms & TV lounges up to 50m2 (7m x
- PDA103 amplifier includes a 3.5mm microphone input, a line level input, an outreach connector and a digital 'TOS' link connector for connection to TV sets or sound bars (requires a separately available TOS-link cable).
- APL outreach plate also supplied for connection to audio sources.
- Metal compensation control helps improve intelligibility in rooms with high metal content.
- Adjustable mic, line level, 'digital' and 'outreach' controls.
- Drive (level) control allows the amplifier's output stage to be set-up to suit the exact characteristics of the application.
- Limit, Peak, Loop Fault and Power On indicators.
- Exceeds the requirements of BS7594 & EN60118-4 when correctly installed.



More Information

Technical Specifications

Type Wall mountable. Plugtop mains lead supplied.

Coverage 50m2 approx.

Plugtop mains lead supplied. Rated supply voltage: 110 to 240Va.c. @ 50/60Hz; Rated power consumption: Mains supply 18W PSU.

Max battery size and type

1 x 3.5mm remote mic. socket; 1 x 3.5mm line level socket, 1 x digital TOS link socket; 1 x Outreach socket. Auxiliary inputs



T 01942 322744

E sales@c-tec.co.uk

F 01942 829867 W www.c-tec.com























Indicators Limit; Peak; Loop Fault; Power On.

Mic; Line; Digital (TOS-Link); Outreach; Metal Compensation (all individually adjustable) and Loop Drive Controls

(Level).

Mic (3.5mm mono jack socket); Line (3.5mm stereo jack socket); Digital (TOS-Link socket); Outreach (4-Connections

way pluggable screw terminal; DC in; Loop (2-way pluggable screw terminal).

Product dimensions (mm) W 135 x H 130 x D 35mm (amplifier only); W 340 x H 250 x D 73mm (kit box).

Construction & finish Black metal. IP Rating IP40.

Weight 380g (amplifier only). 1.45kg (kit box and contents).

Operating conditions/temperature -5 $^{\circ}$ C to +40 $^{\circ}$ C. Max relative humidity: 95%.

PDA103 amplifier c/w digital TOS link connector; PL1/PSU1 plugtop power supply; APL double phone

outreach connection plate; 6m 'Belden' cable; 40m loop cable; 'Hearing Loop Fitted' sticker.















