

## XLR mic level plate (takes AMP microphone)

Part No. **APXM**



### Overview

Accepts balanced or unbalanced microphones with standard 3 pin XLR connectors.

Part of C-TEC's patented 'Outreach Plate' audio input extension system (see key features section below for details).

Compatible with C-TEC's entire range of PDA102, 200E, Pro-Range and ML1 induction loop amplifiers.

Can be connected to any third-party audio or induction loop amplifier using an APV 24V 250mA power supply.

Mounts on a 25mm standard UK single gang back box.

### More Information

The Outreach Plate audio input extension system comprises a range of wall, ceiling and desk mountable plates specifically designed to increase the audio input capability of any audio system. Covering the most common variants of audio connectors, they work by mixing the signals from various audio input sources into a single balanced line level input on a compatible amplifier.

Each input plate features a built-in mixer, preamp, input level control and balanced output.

Typically, up to 10 Outreach plates (any mix) can be daisy-chained to one balanced line level connection with cable lengths up to 100m easily achievable using standard two-pair audio cable (i.e. Belden 8723).

Each plate requires four wires; two balanced line (Line/A +, Line/A -), one ground (GND) and one power connection (V+ = 12-32V d.c.).

Most of C-TEC's PDA Range induction loop amplifiers are fitted with an Outreach connection socket as standard. For audio systems that do not have an Outreach socket, straightforward network connection can be achieved using an 'APV' 24V 250mA d.c. regulated power supply and an 'APXO' 3 pin XLR balanced line output plate.

### Technical Specifications

Power requirements	Supply volts: 12-32V regulated d.c.; Supply current: 12-15mA.
Controls	Adjust input level.
Input signal level	-50dBv (5mV mic)
Gain	55dB.
Level control	0dB to -46dB



Input impedance	500
Phantom volts	8V/0V (link selectable)
Signal to noise ratio	Greater than 75dB
THD + noise	Less than 0.02%
Product dimensions (mm)	W 85 x H 85 x 15 D mm. Mount on a standard 25mm single gang UK back box.
Construction & finish	Plastic.
IP Rating	IP20.
Weight	TBC
Operating conditions/temperature	-5°C to +40°C. Max relative humidity: 95%.



T 01942 322744 E sales@c-tec.co.uk  
F 01942 829867 W www.c-tec.com



C-TEC, Challenge Way, Martland Park, Wigan, WN5 0LD United Kingdom