



# 5MP AI Motorised IR Turret Camera

CODE: CTX-5MP-IPC-TUR3-MW-V2



Motorised  
Lens



5MP  
Resolution



40m IR  
Range



People and  
Vehicle Detection



AI  
Features



## Camera

Image Sensor	1/2.7" CMOS
Image Resolution	5MP (2960 x 1668)
ROM	128MB
RAM	512MB
Scanning System	Progressive
Electronic Shutter Speed	Auto / Manual; 1/3s to 1/100,000s
Minimum Illumination	0.005 lux @ F1.5 (Colour, 30 IRE); 0.0005 lux @ F1.5 (Black / White, 30 IRE); 0 lux (Illuminator On)
S/N Ratio	>56dB
Illumination Distance	40m (131.23 ft.)
Illuminator On / Off Control	Auto / Manual
Illuminator Number	2 (IR LED)
Pan / Tilt / Rotation Range	Pan: 0°–360°; Tilt: 0°–78°; Rotation: 0°–360°



# 5MP AI Motorised IR Turret Camera

CODE: CTX-5MP-IPC-TUR3-MW-V2

## Lens Information

Lens Type		Motorised Varifocal			
Lens Mount		ø14			
Focal Length		2.7mm to 13.5mm			
Maximum Aperture		F1.5			
Field of View		Horizontal: 99°–28°; Vertical: 71°–21°; Diagonal: 134°–35°			
Iris Control		Fixed			
Close Focus Distance		0.8m (2.62 ft.)			
DORI Distance	Lens	Detect	Observe	Recognise	Identify
	W	64m (209.97 ft.)	25.6m (83.98 ft.)	12.8m (41.99 ft.)	6.4m (21 ft.)
	T	210m (688.98 ft.)	84m (275.59 ft.)	42m (137.8 ft.)	21m (68.9 ft.)

## Intelligent Functions

IVS (Perimeter Protection)	Tripwire & Intrusion (Classification and Detection of People & Vehicles)
AI SSA	Supported
Quick Pick (with AI NVR)	Picks up People & Vehicles of Interest from Recorded Events
Smart Search (with AI NVR)	Refined Intelligent Search, Event Extraction and Merging of Event Footage


## Video

Video Compression	H.265 / H.264 / H.264H / H.264B / MJPEG (Only Supported by Sub-Stream)
Smart Codec	Smart H.265+ / Smart H.264+
AI Coding	AI H.265 / AI H.264



# 5MP AI Motorised IR Turret Camera

CODE: CTX-5MP-IPC-TUR3-MW-V2

 Video (continued.)

Video Frame Rate	<p><b>Main Stream:</b> 2880 x 1620 @ (1-20 fps) / 2960 x 1668 @ (1-20 fps) / 2668 x 1520 @ (1-25 / 30 fps)</p> <p><b>Sub Stream 1:</b> 704 x 576 @ (1-25 fps) / 704 x 480 @ (1-30 fps)</p> <p><b>Sub Stream 2:</b> 1920 x 1080 @ (1-25/30 fps)</p>
<i>(These values are the maximum frame rates of each stream. For multiple streams, the values will be subjected to the total encoding capacity.)</i>	
Stream Capability	3 Streams
Resolution	<p><b>5MP</b> (2880 x 1620 / 2960 x 1668); <b>4MP</b> (2688 x 1520); <b>3.6MP</b> (2560 x 1440); <b>3MP</b> (2048 x 1536); <b>3MP</b> (2304 x 1296); <b>1080P</b> / <b>2MP</b> (1920 x 1080); <b>1.3MP</b> (1280 x 960); <b>720P</b> (1280 x 720); <b>D1</b> (704 x 576 / 704 x 480); <b>CIF</b> (352 x 288 / 352 x 240); <b>VGA</b> (640 x 480)</p>
Bit Rate Control	CBR / VBR
Video Bit Rate	H.264: 3 kbps to 8192 kbps; H.265: 3 kbps to 8192 kbps
Day / Night	Auto (ICR), Colour or Black / White
BLC	Supported
HLC	Supported
WDR	120 dB
Scene Self Adaptation (SSA)	Supported
White Balance	Auto, Natural, Street Lamp, Outdoor, Manual, Regional, Custom
Gain Control	Auto
Noise Reduction	3D NR
Motion Detection	On / Off (4 Rectangular Areas)
Image Stabilisation	Electronic Image Stabilisation (EIS)
Region of Interest (RoI)	Supported (4 Areas)
Defog	Supported
AFSA	Supported



# 5MP AI Motorised IR Turret Camera

CODE: CTX-5MP-IPC-TUR3-MW-V2

## Video (continued.)

Image Rotation	0° / 90° / 180° / 270° (Supports 90° / 270° with 4MP Resolution (2688 x 1520) and Lower)
Mirror	Supported
Privacy Masking	Supported (4 Areas)

## Audio

Built-In Microphone	Yes
Audio Compression	G.711a; G.711Mu; PCM; G.726; G.723

## Alarm

Alarm Event	<p><b>Alarm in Case Of:</b></p> <ul style="list-style-type: none"> <li>- No SD Card</li> <li>- Full SD Card</li> <li>- SD Card Error</li> <li>- Network Disconnection</li> <li>- IP Conflict</li> <li>- Illegal Access</li> <li>- Motion Detection</li> <li>- Video Tampering</li> <li>- Intrusion</li> <li>- Tripwire</li> <li>- Scene Change</li> <li>- Audio Detection</li> <li>- Voltage Detection</li> <li>- Defocus Detection</li> <li>- People &amp; Vehicle Detection</li> <li>- Safety Exception</li> </ul>
-------------	--

## Network

Network Port	RJ45 (10 / 100 Base-T)
SDK & API	Supported
Network Protocol	IPv4; IPv6; HTTP;TCP; UDP; ARP; RTP; RTSP; RTCP; RTMP; SMTP; FTP; SFTP; DHCP; DNS; DDNS; QoS; UPnP; NTP; Multicast; ICMP; IGMP; NFS; SAMBA; PPPoE; SNMP
Cyber Security	Video Encryption; Firmware Encryption; Configuration Encryption; Digest; WSSE; Account Lockout; Security Logs; IP / Mac Filtering; Generation and Importing of X.509 Certification; Syslog; HTTPS; 802.1x; Trusted Boot; Trusted Execution; Trusted Upgrade
Interoperability	ONVIF (Profile S/Profile G/Profile T); CGI; P2P; Milestone; Genetec



# 5MP AI Motorised IR Turret Camera

CODE: CTX-5MP-IPC-TUR3-MW-V2

## Network (continued.)

User / Host	20 (Total Bandwidth: 64MB)
Storage	FTP; SFTP; Micro SD Card (Max. 256 G); NAS
Browser	IE11; Chrome; Firefox
Management Software	λ   Cortex VMS
Mobile Client	iOS & Android

## Certification

Certifications	<ul style="list-style-type: none"> <li>- CE-LVD: EN62368-1</li> <li>- CE-EMC: Electromagnetic Compatibility Directive 2014/30/EU</li> <li>- FCC: 47 CFR FCC Part 15, Subpart B</li> <li>- UL/CUL: UL62368-1 &amp; CAN/CSA C22.2 No. 62368-1-14</li> </ul>
----------------	---

## Parameters & Dimensions

Power Supply	12VDC / PoE (802.3af)
Power Consumption	<b>Standard:</b> 5.7W (12 VDC); 6.4W (PoE) <b>WDR + IR Intensity + Intelligent Features:</b> 8.9W (12 VDC); 10.2W (PoE)
Storage Temperature	-40°C to +60°C (-40°F to +140°F)
Working Temperature	-30°C to +60°C (-22°F to +140°F)
Working Humidity	Less than 95% (RH)
Protection	IP67
Casing	Metal
Product Dimensions (L x W x H)	108.3mm x Φ122mm (4.26" x Φ4.80")
Net Weight	715g (1.58lb)
Gross Weight	915g (2.02lb)