VIPER-NVR-4K-8BB

4K 8CH POE NETWORK VIDEO RECORDER





- 4CH 8MP/6MP/5MP/4MP/3MP/1080P/1280x1024/960P/720P/960H/D1/CIF IP input
- H.265 & H.264 high-profile coding
- Intuitive and user-friendly Graphic User Interface (GUI);
 Windows style operation by mouse
- Multi-mode recording: manual / timed / motion / sensor / smart events
- 8CH simultaneous playback
- Search: time slice, time, event, tag and smart search
- Supports face detection and comparison
- Supports multiple VCA (Video Content Analytics) events, such as object abandoned/ missing, region intrusion, tripwire, video exception, etc.
- Supports POS information overlay on live view and playback
- Express and flexible backup via USB, network etc.
- Pentaplex : preview, record, playback, backup and remote access
- DHCP, DDNS, PPPoE network protocol
- Remote control via Web Client or CMS
- Dual stream technology for local storage with high definition









HD IPC

DDNS

Network

PTZ









Audio

MIC

Mobile

CMS









USB

Mouse

E-mail

STD



VIPER-NVR-4K-8BB



| Specification | VIPER-NVR-4K-8BB |
|--|---|
| System | |
| OS | Embedded Linux |
| Video | |
| IP Video Input | 8CH IPC input |
| Incoming/Outgoing Bandwidth | 80Mbps / 80Mbps |
| IP Video Input Resolution | 8MP/6MP/5MP/4MP/3MP/1080P/ 1280×1024/960P/ 720P/960H/D1/CIF |
| Output | HDMI : 3840×2160/1920×1080/1280×1024/ 1024×768 VGA : 1920×1080/1280×1024/1024×768 |
| Audio | VGA . 1920×1080/1280×1024/1024×708 |
| Network Input | 8CH IPC audio input |
| 2-Way Audio | RCA x1 |
| Local Output | RCA x1 |
| Compression | G.711(U/A) |
| Recording | |
| Record Stream | Dual stream recording |
| Resolution | 8MP/6MP/5MP/4MP/3MP/1080P/ 1280×1024/960P/ 720P/960H/D1/CIF |
| Playback | |
| Simultaneous Playback | Max. 8CH |
| Search | Time slice / time / event / tag / smart search |
| Smart Search | Highlighted color to display the camera record |
| | in a certain period of time, different colors refers to different record events |
| | Play, pause, FF, FB, digital zoom, etc. |
| | riay, pause, rr, rb, digital 200111, etc. |
| Decoding Capability Live View/Playback | 1CH OMB. ACH 1000B |
| Alarm | 1CH 8MP; 4CH 1080P |
| Mode | Manual, motion, exception, smart event |
| Input | IPC alarm input |
| Output | IPC alarm input |
| Triggering | Record, snapshot, preset, e-mail, etc. |
| mygemig | record, mapanor, preser, e-mail, etc. |

| Network | |
|-------------------------------|--|
| Interface | DIAE: 10/100/1000 Mbms |
| Interrace | RJ45; 10/100/1000 Mbps |
| Protocol | TCP / IP, PPPOE, DHCP, DNS, DDNS, UPnP, NTP, |
| | SMTP, RTSP, HTTP, HTTPs, 802.1x etc. |
| Mobile Device | |
| OS | iOS/Android |
| Storage | |
| HDD Interface | SATA 3.0 x1, up to 8TB |
| Backup | |
| Local Backup | U disk, USB mobile HDD |
| Network Backup | Yes |
| Port | |
| PoE | RJ45 100Mbps x8 |
| Standards | IEEE802.3af |
| Output Power | ≤ 96W |
| Other | |
| Power Supply | DC48V/2.5A |
| Consumption | ≤ 10W (without HDD) |
| Dimensions (mm) | 300 x 249 x 45 (WxDxH) |
| Working Environment | -10 ~50°C; 10% ~ 90% humidity |
| Certificate | CE, FCC |
| Environment Protection | Directive EU RoHS, REACH and WEEE |

300mm 248.5mm