



5" AI Auto Tracking PTZ Camera

CODE: PTZVIP-5-4K-32X



VSA People & Vehicle



Deep-Learning AI Features



200m IR Range



Triple Stream Support

Camera

Image Sensor	1/2.8" CMOS
Video Compression	H.265+ / H.265 / H.264+ / H.264
Resolution	8MP, 4MP, 2MP (1 to 25fps)
Minimum Illumination	0.01 lux at F1.2 (AGC on); 0.02 lux at F1.2 (AGC on); 0 lux with IR or LED
IR Range	200m
Lens Focus Length	4.8mm to 154mm
Optical Zoom	32x
Field of View	Horizontal: 61.3° to 2.18° Vertical: 36.9° to 1.22° Diagonal: 68.4° to 2.5°
Pan & Tilt Speed	0.5° to 120°/s (Preset Speed: 150°/s)
Pan Range	360°
Tilt Range	-5° to 90° (Auto-Flip)
S/N Ratio	≥52dB
Image Correction	BLC, HLC, WDR, 3D DNR

Interfaces

Detect	4.8mm (Min.)	138m (453.5ft.)
	154mm (Max.)	3528m (11575 ft.)
Observe	4.8mm (Min.)	54.76m (179.66ft.)
	154mm (Max.)	1400m (4593 ft.)
Recognise	4.8mm (Min.)	27.7m (90.7 ft.)
	154mm (Max.)	700m (2296ft.)
Identify	4.8mm (Min.)	13.8m (45.35ft.)
	154mm (Max.)	350m (1148ft.)

Interfaces

Network	RJ45 (PoE++ Support)
Audio	1CH audio input & output; 1CH built-in microphone
Storage	Micro SD card slot (supports up to 256GB)
Reset Button	Yes



5" AI Auto Tracking PTZ Camera

CODE: PTZVIP-5-4K-32X



⚙️ Functions (continued)

Heater	Yes
Fan	Yes
Water-Removal	Hot Air Frost & Ice Removal
Remote Monitoring	SuperLive Plus Mobile App / NVMS (used with Viper NVR)
Network Protocol	HTTP, HTTPS, IPv4/IPv6, 802.1x, QoS, FTP, SMTP, UPnP, SNMP, DNS, DDNS, NTP, RTSP, RTCP, RTP, TCP/IP, UDP, DHCP, PPPoE
Interface Protocol	ONVIF, API & SDK
AI Events	Auto-Tracking, Line Crossing Detection, Exception Detection, Road Traffic Tracking, Region Intrusion Detection (People & Vehicle), Face Detection & Capture

+ Compatible Accessories



Ceiling Mount Bracket

CODE: PTZVIP-IR5-CEILING



Corner Mount Bracket-

CODE: PTZVIP-IR5-CORNER



Pole Mount Bracket

CODE: PTZVIP-IR5-POLE

📏 Parameters & Dimensions

Power Supply	DC24V / AC24V / PoE++
Power Consumption	< 34W
Operating Environment	Temperature: -40°C to +65°C; Humidity: Less than 90% (non-condensing)
Storage Environment	Temperature: -40°C to +70°C; Humidity: Less than 95% (non-condensing)
Dimensions	Ø196mm x 317mm
Weight	3.7kg
Protection Grade	IP66, IK10 (Excluding Glass Window) and 6000V Lighting Protection
Certificate	UKCA, CE, FCC, PSTI 2023, RoHS, WEEE, REACH (EC1907/2006)



Wall Bracket (use with Pole Bracket)

CODE: PTZVIP-IR5-ARM



PTZ Network Keyboard

CODE: VIP-IPKEYBOARD-S2